

**RECEIVED
CENTRAL FAX CENTER**

Amendment
Serial No. 10/763,985

Docket 5000-1-507

OCT 25 2007

IN THE CLAIMS:

Kindly replace the claims of record with the following full set of claims:

1-5 (Canceled)

6. (Currently amended) A transmission apparatus for use in an optical subscriber network, having a plurality of optical network units (ONU), the ONU further comprising:
an synchronous transport module (STM) unit for transmitting an optical signal;
a high-level data link control (HDLC) packet processing unit disposed inside the ONU, for receiving optical signals from the STM unit, the HDLC packet processing unit further including:

an multi-program transmission stream (MPTS) data receiver for receiving the optical signal from the STM unit, for converting the received optical signal into an electrical signal and outputting an HDLC packet;

an MPTS data extractor coupled to the MPTS receiver, for receiving the HDLC packet from the MPTS data receiver, removing overhead from the HDLC packet and extracting MPTS data;

a buffer coupled to the MPTS data extractor, for buffering the extracted MPTS data;

a controller for controlling the MPTS receiver, the MPTS data extractor and the buffer; and

a switching unit for switching the MPTS data from the HDLC packet processing unit to a plurality of subscribers, said switching unit comprising:

a first memory for storing the MPTS data; and

Amendment
Serial No. 10/763,985

Docket 5000-1-507

a plurality of secondary memory units having assigned storage areas,
defined by an address, dependent upon the MPTS data associated with a
corresponding subscriber in the first memory and
means for outputting the stored MPTS data to a corresponding one of the
plurality of subscribers by said subscriber accessing said address in said
secondary memory.

7. (Previously presented) The transmission apparatus as claimed in claim 6,
wherein the buffer continuously outputs the MPTS data.

8. (Cancelled).

9. (Currently amended) The transmission apparatus as claimed in claim [[8]] 6,
wherein the plurality of subscribers access the MPTS data based upon predetermined
requirements of each subscriber.

10. (Cancelled).

11. (Currently amended) The transmission apparatus as claimed in claim 6,
wherein the HDLC protocol provides for a HDLC packet of a size of 64 Bytes byte to
1024 Bytes byte of a ATM payload.

12. (Cancelled)

13. (Previously presented) The transmission apparatus as claimed in claim 6,
wherein the transmission apparatus provides for a payload transmission rate of 6:512.

Amendment
Serial No. 10/763,985

Docket 5000-1-507

14. (Currently amended) The transmission apparatus as claimed in claim
[[8]] 6, wherein the plurality of secondary memory units is configured for
outputting or discarding first-inputted MPTS data according to a first-in first-out
(FIFO) method.